

ELITE series

650VA / 360W 850VA / 480W
1200VA / 600W 1500VA / 900W 2200VA / 1200W



Line-Interactive UPS

Features:

- Built-in voltage regulator for reliable power quality
LCD Display Shows Live UPS Status
Energy Saving Compact Design
2 Year Advanced Replacement Warranty
- Line Interactive UPS with simulated sinewave output
- Excellent microprocessor control guarantees high reliability
(Internal self-diagnostic technology)
- Boost and buck AVR for voltage stabilization
(Wide input range with two boost and one buck control)

Technical Specification:

MODEL	ES650-AVR	ES850-AVR	ES1200-AVR	ES1500-AVR	ES2200-AVR
CAPACITY (VA/W)	650/360	850/480	1200/720	1500/900	2200/1200
INPUT					
Voltage (Vac)	240				
Voltage Range (Vac)	177~290				
OUTPUT					
Nominal Voltage (Vac)	240				
Voltage Regulation	±10% (Battery Mode)				
Frequency Range (Hz)	50/60				
Frequency Regulation (Hz)	±1 (Battery Mode)				
Transfer Time (ms)	Typical 2-6				
Waveform	Stepped Sine Wave				
BATTERY					
Type (Lead-acid) (V/Ah)	12/7*1	12/9*1	12/7*2	12/9*2	12/9*2
PHYSICAL					
Dimension (D*W*H) (mm)	298*101*142		353*149.3*162	380*158*198	
Net weight (kg)	4.4	5.2	7.85	9.4	10.4
ENVIRONMENT					
Operating environment (°C)	0 to 40				
Noise Level(Less than) (dB)	45		45		55

Rear Panel

