

# RTX series

1500VA/1350W 2000VA/1800W 3000VA/2700W



## Line-Interactive UPS

### Features:

- High output power factor (0.9)
- Built-in voltage regulator stabilises unstable AC input power
- Intelligent communication slot enables remote monitoring
- HID USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS and Linux
- Rack/tower dual set-up with rotatable LCD panel
- 2 Year Advanced Replacement Warranty

# Technical Specification:

MODEL	RTX1500LCD	RTX2000LCD	RTX3000LCD
CAPACITY	1500VA/1350W	2000VA/1800W	3000VA/2700W
INPUT			
Voltage	230 VAC		
Voltage Range	161~276VAC		
OUTPUT			
Nominal Voltage	230Vac		
Voltage Regulation	+/- 5% (Battery mode)		
Frequency Range	50/60Hz		
Frequency Regeulation	±0.1Hz (Battery mode)		
Transfer Time	Battery Mode ↔ LineMode	Typical	2-6 ms
Waveform	Pure sine wave		
BATTERY			
Type (Lead-acid)	12V/9Ah*3	12V/7Ah*6	12V/9Ah*6
PHYSICAL			
Dimension (D*W*H)	436mm*438mm*86.5mm	608mm*438mm*86.5 mm	
Net weight	18kg	28kg	31kg
ENVIRONMENT			
Operatingenvironment	0° to 40° C		
Noise Level(Less than)	45dB		

## Rear Panel

